

The flexible comprehensive solution: BOGE C 15 DR




Modular system allows
customised configuration!



CONFIDENTLY CONTROLLED

The **base** control unit with LC display and pressure sensor system is included as standard. However, the **focus** 2.0 control unit is also available as an option, with its integrated efficiency indicator, well-proven BOGE leakage monitor and even an RFID input.



PERFECTLY INTEGRATED

The C series compressors are intelligently designed, with all of the essential components integrated in the compact module. The lack of hoses and connection pipes makes it practically impossible for leaks to occur. Pressure losses are also minimised.



HIGHLY EFFICIENT

High free air delivery rates achieved with particularly low power input – this is the trademark of the special BOGE air end of the C series compressors. The top efficiency ratings are also partly due to the intelligent arrangement of the components. All in the interest of producing consistently high-quality compressed air.



EFFECTIVELY UNITED

Where space is at a premium: the C 15 DR combines a dryer and tank with a remarkable small footprint, combined with exceptionally low sound pressure levels it can be installed even within the workplace. Numerous treatment and filtering options make the system a flexible all-rounder.

Wherever space plays a role, the BOGE C 15 DR comes into its own, because its small footprint allows it to be installed, right where it is needed. Each of the individual elements – from the receiver to the optional dryer and oil/water separator – come ready assembled and are delivered as a compact unit, ready for connection. In addition, the super silenced sound insulation ensures particularly quiet running.

**BOGE Compressed Air Systems
GmbH & Co. KG**

P.O. Box 10 07 13 · 33507 Bielefeld
 Otto-Boge-Straße 1–7 · 33739 Bielefeld
 Tel. +49 5206 601-0 · Fax +49 5206 601-200
 info@boge.de · www.boge.de

YOUR NEEDS DICTATE

The C 15 DR meets your each and every need: in addition to a selection of receiver sizes, you have the option of including a refrigerant dryer, oil/water separator, integrated filters and even an intake air filter. The pre-assembled pipework ensures that both the installation work and the space required are kept to an absolute minimum.



No matter what your main priorities are – the number of options available covers all of your requirements.



With its super silenced sound insulation and extremely compact design, the BOGE C 15 DR can be installed directly within the workplace.

FROM THE PROFILE OF A TRUE ALL-ROUNDER

BOGE Model	Max. pressure*		Effective free air delivery**		Motor power		Dimensions W x D x H mm	Weight kg
	bar	psig	m ³ /min	cfm	kW	HP		
C 15 DR	8	115	1,74	61	11	15	1940 x 1000 x 1990	650
C 15 DR	10	150	1,53	54	11	15	1940 x 1000 x 1990	650
C 15 DR	13	190	1,33	22	11	15	1940 x 1000 x 1990	650

* Max. pressure of the compressor. ** Free air delivery for the complete package in accordance with ISO 1217, Appendix C, at 20°C ambient temperature and maximum pressure.

Please also take a look at our other models in the C series, all of which can be found in the C series brochure.